

X16

Small Office Digital System

Features

- 4 CO Lines (total 6 Lines with optional expansion)
- 2-Line Expansion Module for CO or VoIP (Option)
- 16 Extensions
- Auto Attendant System
- 4-Port Voice Mail System
- Caller ID
- Music on Hold
- 2 Conference Circuits
- User-friendly telephone
- Navigation Key
- Easy Installation
- System Programming by Phone
- Call Hold, Transfer, Forward, Waiting, 3-way Conference



Overview

The X16 is a fully featured, multi-line business phone ideally suitable for home or small office use. The X16 provides a powerful level of communication sophistication and efficiency. It is designed to receive up to 6 regular telephone lines. Alternately, 2 of the optional line circuits can be used for Voice over IP linkup. With a sophisticated design, it can support versatile features, high performance and outstanding capability. Up to 16 fully-functional digital key telephones can be connected to the system more easily than in any other application thus making the X16 the perfect SOHO, SMB and SME communications solution.

X16

Small Office Digital System

Specifications

Compliant Standard

- 6 FXO Ports (PSTN Lines)
- ITU-T G.984.1, 984.2, 984.3, 984.4
- IEEE 802.1p
- IEEE 802.1Q
- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3z

Quality of Service (QoS)

- Port-based VLAN
- Q-in-Q VLAN
- Strict Priority
- Weighted Round-Robin priority
- IGMP filtering & snooping
- Multicasting IGMP v1,v2,v3

I/O ports for KSU:

- 4 PSTN Ports : L1/L2, L2, L3/L4, L4
- 4 Digital Ports for 16 Phones
- Expansion Board Option 1 for 2 PSTN Ports (L5/L6, L6) or
- Option 2 for 2-Line VoIP
- 1 Music Port (Music on Hold)
- 1 PFT Port (PSTN 1)
- Reset button for factory default setting

I/O ports for Phone:

- Headset Jack (2.5mm) & Handset Jack
- RJ 11 to KSU

Voice Handling

- Distinctive ringing and programmable tone/ring support
- Enhanced voice quality setting for handset, headset and hands-free

Keys (46 keys)

- 6 CO line Keys w/ dual color (Green & Blue) LED
- 3 Function Keys (Phone Book, Caller ID, Program)
- 12 Programmable Feature Keys (w/ LED)
- Speaker (w/ LED), Mute(w/ LED), Redial, Hold, Feature, Transfer, Delete, Conference



Dialing methods

- Redial, Mute, Call log, Phone book, speed dial
- 4-Line or 6-Line dialing

Configuration and Management

- Auto Installation
- Customization database

Display

- 2 x 16 Character-based LCD display with Blue Backlight
- 6 dual color LED (Blue and Green)
- 12 Feature Keys with Blue LED

Physical Spec (KSU, Phone)

- Power Supply of KSU: 30 V, 2 A switching power adapter
- Operating Temperature: 0°C to 40°C
- Operating Humidity: 10% to 90% (non-condensing)
- Dimension (KSU): 340.3 x 208.3 x 48.8 mm³
- Dimension (Phone): 214 x 192 x 64 mm³

Phone Features

- Trilingual Display
- 2 * 16 Characters LCD with Blue Backlight
- Programmable Feature Keys
- Voice Mail
- Individual Mail Box and Greeting
- Caller ID Data Base (50 Records)
- Phone Book (50 Records)
- Speed Dial Key for Intercom/CO Call
- 3-Way Conference
- Speakerphone
- Easy Transfer
- Auto Hold/Hold Release
- Mute/Flash/Pause/Redial
- Call Forward
- Do Not Disturb
- Digital Ringer/Voice Volume Control
- Ringer On/Off
- Feature Programming

Copyright © 2011 Tecom Co., Ltd. All rights reserved. Tecom's logo is a registered trademark of Tecom Co., Ltd. All specifications are subject to change without notice.